

Doubles up as a dependable end link.


High-grade stainless steel yields a result that outshines the rest: This stainless master link is electrically welded for a clean finish, stamped and suitable for both I- and II-leg assemblies and wire rope slings (similar to DIN 3088- 1989). The master link may also be used in VWI four-leg assemblies and as an end link. Its dimensions are similar to DIN 5688-1 and it is tested at 100 % of its load capacity.

A particular bonus is the higher resistance to acids and caustics compared to the standard loading rings G8, G10 and G12. The stamp makes the master link clearly identifiable. The master link also bears the CE-mark.

The AWI Master link is particularly suited for use in water and wastewater applications. It can also be used in connection with chemicals and food products; however, restrictions will apply.



AWI Master link



Code	Load capacity 0°-45° [kg]	Fits on single hook acc. DIN 15401 no.	For 1-leg slings	For 2-leg slings	Fits on double hook acc. DIN 15402 no.
AWI 8-6	560	0.50	4	4	-
AWI 10-6	850	1.60	5	5	2.50
AWI 13-6	1,600	2.50	6/7/8	6	4
AWI 16-6	2,600	2.50	10	7/8	4
AWI 18-6	3,500	5	-	10	6
AWI 22-6	6,300	6	13/16	13	8
AWI 26-6	8,900	8	20	16	10
AWI 32-6	13,200	10	-	20	12
AWI 36-6	14,700	16	-	-	20
AWI 45	12,000	25	26	-	32

Code	d [mm]	w [mm]	s [mm]	Weight [kg/pc.]
AWI 8-6	8	35	-	0.08
AWI 10-6	10	50	-	0.16
AWI 13-6	13	60	10	0.34
AWI 16-6	16	60	14	0.53
AWI 18-6	18	75	14	0.83
AWI 22-6	23	90	17	1.55
AWI 26-6	27	100	20	2.46
AWI 32-6	32	110	26	3.86
AWI 36-6	36	140	29	6.22
AWI 45	45	180	-	12.82

Custom-made, also with flattening available.