

# pewag BWI Transition link

## Electrically welded for an extra-clean finish.

A higher resistance to acids and caustics compared to the standard transition links G8, G10 and G12 is just one of the many benefits that make this stamped transition link truly remarkable. The use of high-grade stainless steel also ensures that this electrically welded transition and securing link will never rust.

The stamp and the CE-mark ensure that the product is clearly identifiable. The transition link is part of welded assemblies, may also be used as an end link and is tested at 100 % of its maximum load capacity. Its dimensions are similar to DIN 5688-1.

The outstanding quality of this transition link is also reflected in its wide range of possible applications: It may be used as a connecting link for assembling I- to IV-leg assemblies in welded systems as well as an end link. In addition, it is ideally suited for use in water and wastewater applications and can also be used in connection with chemicals and food products; however, restrictions will apply.



BWI Transition link

Code	Load capacity 0°-45° [kg]	d [mm]	t [mm]	w [mm]	s [mm]	Weight [kg/pc.]	For 1-leg slings	For 2-leg slings
BWI 7-6	900	7	36	16	-	0.04	5/6	5/6
BWI 9-6	1,250	9	44	20	-	0.07	7	7
BWI 10-6	1,600	10	44	20	-	0.09	8	8
BWI 13-6	2,500	13	54	25	10	0.18	10	10
BWI 16-6	4,250	16	70	34	14	0.35	13	13
BWI 20-6	6,300	20	85	40	16	0.67	16	16
BWI 22-6	8,000	23	115	50	17	1.16	20	-
BWI 26-6	10,070	27	140	65	20	1.92	-	-
BWI 32-6	12,000	32	150	70	26	3.18	26	-

Custom-made, also with flattening available.

