

480kg

Power supply		120V or 240V 50Hz/60Hz						
Type		Single speed type			Dual speed type			
Product code		ED48S	ED48S+PT*3	ED48S+GT*4	ED48ST	ED48ST+PT*3	ED48ST+GT*4	
Rated load (W.L.L.)	(kg)	480						
Motor output	(W)	600						
Short time rating	(min)	15						
Intermittent rating	%ED	30						
	Max.number of starts per hour	180						
Rated current	(A)	120V		10				
		240V		5				
Lifting speed	(m/min)	High		6.7				
		Low		—		2		
Standard lift	(m)	3						
Push button cord length	L (m)	2.5						
Hand chain folded length	(m)	—		2.7	—		2.7	
Load chain diameter	(mm)	4						
Mass [net weight]	(kg)	21(21.5)*2	25(25.5)*2	34(34.5)*2	21(21.5)*2	25(25.5)*2	34(34.5)*2	
Headroom	C (mm)	520		535	520		535	
Flange width adjustability B	(mm)	—	50 to 102	75 to 125	—	50 to 102	75 to 125	
Minimum radius for curve	(mm)	—	1100	1300	—	1100	1300	
Dimensions	(mm)	k		454	469	454		469
		g		24	24	24		24
		—	204	345	—	204	345	
		—	182	236	—	182	236	
		—	46	152	—	46	152	
		—	82	106	—	82	106	
		—	60	71	—	60	71	
		—	19	28	—	19	28	
		—	76	95	—	76	95	
		s'	—		106	—		106
		m	—	47.5	56	—	47.5	56
		n	—	84	112	—	84	112
		o	—	42	50	—	42	50
		p	—	10	10	—	10	10
		q	—	54	69	—	54	69
		r	—	38	50	—	38	50
		t	—	22	25	—	22	25
	u	—		183	—		183	