

# 60kg to 240kg

Power supply		120V or 240V 50Hz/60Hz															
Type		Single speed type					Dual speed type					Cylinder type					
Product code		ED06S	ED10S	ED18S	ED16S	ED24S	ED06ST	ED10ST	ED18ST	ED16ST	ED24ST	EDC06SD	EDC10SD	EDC18SD	EDC16SD	EDC24SD	
Rated load (W.L.L.) (kg)		60	100	180	160	240	60	100	180	160	240	60	100	180	160	240	
Motor output (W)		300			600		300			600		300			600		
Short time rating (min)		15(20)* <sup>1</sup>		10(15)* <sup>1</sup>		20		15(20)* <sup>1</sup>		10(15)* <sup>1</sup>		20		15(20)* <sup>1</sup>		10(15)* <sup>1</sup>	
Intermittent rating	%ED	30		20		30		30		20		30		20		30	
	Max.number of starts per hour	180		120		180		180		120		180		120		180	
Rated current (A)	120V	5		6		10		5		6		10		5		6	
	240V	3			5		3			5		3			5		
Lifting speed (m/min)	High	21	13	8	20	13.5	21	13	8	20	13.5	21	13	8	20	13.5	
	Low	—	—	—	—	—	4	3	3	4	3	4	3	3	4	3	
Standard lift (m)		3				3						1.8					
Push button cord length L(m)		2.5				2.5						—					
Load chain diameter (mm)		4				4						4					
Mass [net weight] (kg)		11.5 (12)* <sup>2</sup>			15.5 (16)* <sup>2</sup>		12 (12.5)* <sup>2</sup>			16 (16.5)* <sup>2</sup>		14.5 (15)* <sup>2</sup>			18.5(19)* <sup>2</sup>		
Headroom C (mm)		315			330		315			330		945			960		
Dimensions (mm)	a	371 (364)* <sup>1</sup>			428		371 (364)* <sup>1</sup>			428		371 (364)* <sup>1</sup>			428		
	d	187			205		187			205		187			205		
	e	184 (177)* <sup>1</sup>			223		184 (177)* <sup>1</sup>			223		184 (177)* <sup>1</sup>			223		
	f	205			219		205			219		205			219		
	h	125			135		125			135		125			135		
	i	80			84		80			84		80			84		
	g	25				25						25					
	j	25				25						25					
	k	340			362		340			362		340			362		
	m	92				92						92					
	n	73				73						73					