

02.4 FLAT SLINGS

Liftfix flat sling, 2-ply
0,5 - 10,0 t

- Sectional loop reinforcement
- 2-ply, tear-resistant label



Liftfix HB – flat sling with solid basic equipment

With Liftfix we offer you a flat sling in the usual standard quality with different load capacities ranging from 0.5 t to 10 t. Of course Liftfix is manufactured in accordance with DIN EN 1492-2 and is equipped with a 2-ply label with the writing protected inside. Sectional reinforcement of the flat sling loop protects the sling in the critical area – where it meets the crane hook. Standard-compliant colour coding also prevents confusion of the load capacity.

Nominal carrying capacity [kg]	Loop width [mm]	Loop length [mm]	L1 min. [m]	Strap width [mm]	Strap thickness [mm]	Approx. weight 1st m [kg]	Approx. weight per running m [kg]	Order numbers for standard lengths
								2 m 3 m 4 m 5 m 6 m 8 m
500	36	150	1,0	36	3,0	0,2	0,1	D002558 D002559 D002560 D002561 D002562 D002563
1.000	30	300	1,0	30	5,2	0,2	0,2	D002564 D002565 D002566 D002567 D002568 D002569
1.500	35	300	1,0	50	6,8	0,4	0,3	D002570 D002571 D002572 D002573 D002574 D002575
2.000	40	300	1,2	60	5,0	0,4	0,3	D002576 D002577 D002578 D002579 D002580 D002581
3.000	50	400	1,5	90	5,0	0,6	0,5	D002630 D002631 D002632 D002633 D002634 D002635
4.000	70	400	1,5	120	6,8	0,9	0,8	D002582 D002583 D002584 D002585 D002586 D002587
5.000	80	500	1,7	150	6,6	1,2	1,0	D002588 D002589 D002590 D002591 D002592 D002593
6.000	100	700	2,1	180	7,2	1,4	1,2	D002594 D002595 D002596 D002597 D002598 D002599
8.000	130	800	2,3	240	7,2	1,8	1,6	D002600 D002601 D002602 D002603 D002604 D002605
10.000	160	1.000	2,6	300	7,4	2,4	2,3	- D002606 D002607 D002608 D002609 D002610

1 Special designs available on request. Also available with D-links on request. Manufactured according to DIN EN 1492-2.



The explanations of the icons can be found on the flap.