



SX-flat slings 1,0 - 10,0 t  
with C-link or D-links

- Cut-resistant contact side due to secutex, abrasion-resistant reverse side due to Powerflex
- Tear-resistant label covered with a protective sleeve
- Optional fitting with an RFID transponder

## SX flat slings with a C-link or two D-links






### Rapid noosing with C-link










With the C-link attached to one end you can also use the SX flat sling for lifting in a noose. Inside the hook, the strap has an extensive contact area and the built-in safety catch prevents the strap from slipping out of the attachment point. If the safety catch is damaged, it can easily be replaced at the C-link.

### More possibilities with D-links

With D-links attached to both ends, you have considerably more flexibility. Simply thread one end of the strap through the opposite link – this ensures a lacing in which nothing can slip. Furthermore, the D-link makes it easier to hang the sling into spreader beams or crane hooks when applied in a single layer, as the links do not require a large contact area.



Nominal carrying capacity [kg]	Loop width [mm]	Loop length [mm]	L1 min. [m]	Strap width [mm]	Strap thickness [mm]	Approx. weight 1st m [kg]	Approx. weight per running m [kg]				Order numbers for standard lengths			
								2 m	3 m	4 m	5 m	6 m	8 m	
 <b>1.000</b>	30	300	1,0	30	13,1	1,0	0,4	<b>S000450</b>	<b>S000451</b>	<b>S000452</b>	<b>S000453</b>	<b>S000454</b>	<b>S000455</b>	
 <b>2.000</b>	35	300	1,0	60	13,5	2,7	0,8	<b>S000456</b>	<b>S000457</b>	<b>S000458</b>	<b>S000459</b>	<b>S000460</b>	<b>S000461</b>	
 <b>3.000</b>	50	400	1,0	90	13,9	3,6	1,3	<b>S000401</b>	<b>S000402</b>	<b>S000462</b>	<b>S000463</b>	<b>S000464</b>	<b>S000465</b>	
 <b>5.000</b>	80	500	1,5	150	14,9	10,6	2,2	<b>S000466</b>	<b>S000467</b>	<b>S000468</b>	<b>S000469</b>	<b>S000470</b>	<b>S000471</b>	

Nominal carrying capacity [kg]	L1 min. [m]	Strap width [mm]	Strap thickness [mm]	Approx. weight 1st m [kg]	Approx. weight per running m [kg]				Order numbers for standard lengths		
						2m	3m	4m	5m	6m	8m
 <b>1.000</b>	1,0	30	13,1	1,1	0,4	<b>S000472</b>	<b>S000473</b>	<b>S000474</b>	<b>S000475</b>	<b>S000476</b>	<b>S000477</b>
 <b>2.000</b>	1,0	60	13,5	2,2	0,8	<b>S000478</b>	<b>S000479</b>	<b>S000480</b>	<b>S000481</b>	<b>S000482</b>	<b>S000483</b>
 <b>3.000</b>	1,0	90	13,9	4,0	1,3	<b>S000484</b>	<b>S000485</b>	<b>S000486</b>	<b>S000487</b>	<b>S000488</b>	<b>S000489</b>
 <b>4.000</b>	1,2	120	14,9	5,6	1,8	<b>S000490</b>	<b>S000491</b>	<b>S000492</b>	<b>S000493</b>	<b>S000494</b>	<b>S000495</b>
 <b>5.000</b>	1,5	150	14,9	9,1	2,2	<b>S000496</b>	<b>S000497</b>	<b>S000498</b>	<b>S000499</b>	<b>S000500</b>	<b>S000501</b>
 <b>6.000</b>	1,8	180	15,1	15,1	2,7	<b>S000502</b>	<b>S000503</b>	<b>S000504</b>	<b>S000505</b>	<b>S000506</b>	<b>S000507</b>
 <b>8.000</b>	2,2	240	15,1	23,0	3,8	-	<b>S000508</b>	<b>S000509</b>	<b>S000510</b>	<b>S000511</b>	<b>S000512</b>
 <b>10.000</b>	2,4	300	15,5	34,1	4,8	-	<b>S000513</b>	<b>S000514</b>	<b>S000515</b>	<b>S000516</b>	<b>S000517</b>

**i** Special designs available on request. Manufactured according to DIN EN 1492-2.



The explanations of the icons can be found on the flap.